



Product certificate K109120/01

Issued 01-06-2022

Replaces -

Page 1 of 2

Automatic shut-off (mixing) valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

DELABIE SCS

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K669 "Sanitary tapware: Automatic shut-off (mixing) valves" dated 01-12-2018, which covers the requirements of:

EN816:2017 "Sanitary tapware – Automatic shut-off valves (PN10)"

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.
Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company
DELABIE SCS
18, rue, du Maréchal FOCH
80130 FRIVILLE ESCARBOTIN
France
Tel. +33 322602270



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Automatic shut-off (mixing) valves

PRODUCT SPECIFICATION

The products mentioned below belong to this certificate

Type	Design	Article no.
Automatic shut-off valve	Tempomix 3	794100
	Temposoft	740500

FITNESS FOR CONTACT WITH DRINKING WATER

This products are approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

APPLICATION AND USE


Sanitary tapware; automatic shut-off (mixing) valves are designed for application within the following limits of use:

- a working pressure from 50 kPa up to 1000 kPa;
- a water temperature of maximum 90°C.

The recommended limits for correct operation are:

- a working pressure of 100 kPa up to 500 kPa;
- a water temperature of maximum 65°C.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA" together with the Watermark logo 

Place of the mark: on the body.

Compulsory specifications:

- name or mark of manufacturer, on the body;
- indication for temperature selection, on the handle;
- the acoustic group, if classified, on the body;
- the flow rate class, on the body.

Method of marking:

- non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- DELABIE SCS
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.